

DOUBLE SKINNED AND ACOUSTIC ISOLATED BOX FAN WITH EXTERNAL MOTOR (BACKWARD CURVED PLUG FAN)



MODEL	VOLTAGE (VOLT/Hz)	MOTOR POWER		CURRENT (A)	SPEED (d/d)	AIR FLOW (m3/h)
		HP	kW			
CPH-315	230/380/50	1/3	0,25	1,82	1400	2000
CPH-355	230/380/50	1/2	0,37	2,54	1400	3000
CPH-400	230/380/50	3/4	0,55	3,38	1400	4500
CPH-450	230/380/50	1,5	1,1	7,30	1400	6500
CPH-500	230/380/50	2	1,5	9,20	1400	8500
CPH-560	230/380/50	3	2,2	13,60	1400	10500
CPH-630	230/380/50	4	3	19	1400	12500

DOUBLE SKINNED AND FILTERED BOX FAN WITH EXTERNAL MOTOR (BACKWARD CURVED PLUG FAN)



MODEL	VOLTAGE (VOLT/Hz)	MOTOR POWER		CURRENT (A)	SPEED (d/d)	AIR FLOW (m3/h)
		HP	kW			
CPH-F-315	230/380/50	1/2	0,37	2,54	1400	2000
CPH-F-355	230/380/50	3/4	0,55	3,38	1400	3000
CPH-F-400	230/380/50	1,5	1,1	7,30	1400	4500
CPH-F-450	230/380/50	2	1,5	9,20	1400	6500
CPH-F-500	230/380/50	3	2,2	13,60	1400	8500
CPH-F-560	230/380/50	4	3	19	1400	10500
CPH-F-630	380/50	4	3	-	1400	12500